

CDXconventional

# CCP-KS03

## CONVENTIONAL CALL POINT 3-POSITION KEYSWITCH WITH BACK BOX (ORANGE)

### Features

- ▶ 3 position keyswitch
- ▶ Terminals can accommodate up to a 2.5 mm<sup>2</sup> solid conductor
- ▶ Other colours available on request



### Description

The CCP-KS03 is an orange Conventional call-point based upon the industry standard KAC world series housing and features easy to install, push-fit wiring terminals. The unit features a 3-position keyswitch, marked “AUTO”, “ON” and “OFF” which can be used for control of other equipment. The unit can support either a ‘Frangible Glass’ element or a ‘Non Frangible Plastic’ element.

### Specification

Ordering codes	CCP-KS03
Nominal operating resistance	470 Ω
Maximum contact resistance (R)	200 Ω
Ingress Protection Rating	IP24
Operating Temperature Range	-10 °C to 55 °C
Storage Temperature Range	-10 °C to 55 °C
Maximum Humidity	95%RH - Non condensing (at 40 °C)
Colour / Case Material	Orange / ABS
Weight (g) / Dimensions (mm)	(Flush Mount) 110 / W89 x H93 x D27.5
	(Surface Mount with Back Box) 161 / W89 x H93 x D59.5
Accessories	Frangible Element      KAC/G/HE
	Non-Frangible Element      KAC/EWS/HE