



The flashing enables tight connection of a smoke ventilation window with profiled roof coverings such as tiles and profiled metal sheeting.

Universal flashing, which can be applied not only to corrugated coverings, but to all roof coverings with a profile height of up to 45 mm.

Aluminium apron.

Conservation version available. (black colour)

Installed at depth J (-3cm).

### Installation

Maximum height of roof covering material profile [mm]	45
Window installation depth	J (-3 cm)
Minimum slope angle [°]	20
Maximum slope angle [°]	90

### Others

Flashing type	Standard
Roof covering type	<ul style="list-style-type: none"> <li>• profiled up to 45 mm;</li> </ul>
Flashing destination	<ul style="list-style-type: none"> <li>• for roof window;</li> <li>• for escape window;</li> </ul>

### Apron

Apron material	Aluminum-plastic apron
----------------	------------------------

### Component parts

<b>Main component parts</b>	<ul style="list-style-type: none"> <li>• standard upper element;</li> <li>• standard right side;</li> <li>• standard left side;</li> <li>• frame side covering profiles_standard;</li> </ul>
<b>Additional elements</b>	<ul style="list-style-type: none"> <li>• water drainage gutter; <ul style="list-style-type: none"> <li>• roof rails;</li> </ul> </li> <li>• insulation wedges; <ul style="list-style-type: none"> <li>• hooks;</li> </ul> </li> <li>• fitting instructions;</li> </ul>
<b>Module type</b>	<ul style="list-style-type: none"> <li>• e;</li> </ul>

### Window Material

Sheet thickness [mm]	0,6
Flange material	Blacha aluminiowa RAL 9005

### Technical and electric parameters

Solar powered	No
---------------	----